

## 250 SERIES PTFE (Teflon)Black Braided Hose for 200 & 570 Series



250\_SERIES\_PTFE\_\_519db6850f52f.jpg

250 SERIES PTFE (Teflon)Black Braided Hose for 200 & 570 Series Fittings. Click on image for selection of Sizes & Pricing

Rating: Not Rated Yet

**Price:**

Variant price modifier:

Base price:

Price:

You save:

[Ask a question about this product](#)

Description

AF250-XX-1M-CUT

SOLD IN METER LENGTHS

Aeroflow's 250 Series hose is a durable, professional light weight option that resists leaks and fumes. It's constructed from a PTFE inner liner with a reinforced 308 Stainless Steel layer wrapped in a black nylon outer braid for maximum appearance and abrasion resistance.

- Stainless Steel reinforced middle layer for maximum strength and burst pressure
- Braided Nylon outer shield for abrasion resistance
- Recommended for brake, E85, Alcohol, transmission, clutch, Nitrous, Power Steering, Oil, Hydraulics and Vacuum applications
- Minimum Temp -70°C, Maximum Temp 250°C
- To be used with Aeroflow 200 & 570 Series Fittings

### 250 Series Hose specifications:

AN Size: -3

Hose I.D: 0.14" (3.56mm)

Hose O.D: 0.25" (6.35mm)

Operating Pressure: 4000 psi

Burst Pressure: 12000 psi

\*\*

AN Size: -4

Hose I.D: 0.19" (4.83mm)  
Hose O.D: 0.30" (7.62mm)  
Operating Pressure: 4000 psi  
Burst Pressure: 12000 psi

\*\*

AN Size: -6  
Hose I.D: 0.32" (8.13mm)  
Hose O.D: 0.32" (10.92mm)  
Operating Pressure: 3000 psi  
Burst Pressure: 10000 psi

\*\*

AN Size: -8  
Hose I.D: 0.42" (10.67mm)  
Hose O.D: 0.54" (13.72mm)  
Operating Pressure: 2500 psi  
Burst Pressure: 8000 psi

\*\*

AN Size: -10  
Hose I.D: 0.51" (12.95mm)  
Hose O.D: 0.63" (16.00mm)  
Operating Pressure: 2000 psi  
Burst Pressure: 6000 psi

\*\*

AN Size: -12  
Hose I.D: 0.64" (16.26mm)  
Hose O.D: 0.76" (19.30mm)  
Operating Pressure: 1000 psi  
Burst Pressure: 4000 psi

AF250-03

AF250-04

AF250-06

AF250-08

AF250-10

AF250-12