250 SERIES PTFE (Teflon)Black Braided Hose for 200 & 570 Series



250 SERIES PTFE (Teflon)Black Braided Hose for 200 & 570 Series Fittings. Click on image for selection of Sizes & Pricing

Rating: Not Rated Yet Price: Variant price modifier: Base price:	
Price: You save:	
Ask a question about this product	
Description	
AF250-XX-1M-CUT	
SOLD IN METER LENGTHS	

Aeroflow's 250 Series hose is a durable, professional light weight option that resists leaks and fumes. It's constructed from a PTFE inner liner with a reinforced 308 Stainless Steel layer wrapped in a black nylon outer braid for maximum appearance and abrasion resistance.

- Stainless Steel reinforced middle layer for maximum strength and burst pressure
- Braided Nylon outer shield for abrasion resistance
- Recommended for brake, E85, Alcohol, transmission, clutch, Nitrous, Power Steering, Oil, Hydraulics and Vacuum applications
- Minimum Temp -70°C, Maximum Temp 250°C
- To be used with Aeroflow 200 & 570 Series Fittings

250 Series Hose specifications:

AN Size: -3 Hose I.D: 0.14" (3.56mm) Hose O.D: 0.25" (6.35mm) Operating Pressure: 4000 psi Burst Pressure: 12000 psi

**

AN Size: -4

Hose I.D: 0.19" (4.83mm) Hose O.D: 0.30" (7.62mm) Operating Pressure: 4000 psi Burst Pressure: 12000 psi

**

AN Size: -6 Hose I.D: 0.32" (8.13mm) Hose O.D: 0.32" (10.92mm) Operating Pressure: 3000 psi Burst Pressure: 10000 psi

**

AN Size: -8 Hose I.D: 0.42" (10.67mm) Hose O.D: 0.54" (13.72mm) Operating Pressure: 2500 psi Burst Pressure: 8000 psi

**

AN Size: -10 Hose I.D: 0.51" (12.95mm) Hose O.D: 0.63" (16.00mm) Operating Pressure: 2000 psi Burst Pressure: 6000 psi

**

AN Size: -12 Hose I.D: 0.64" (16.26mm) Hose O.D: 0.76" (19.30mm) Operating Pressure: 1000 psi Burst Pressure: 4000 psi

AF250-03

AF250-04

AF250-06

AF250-08

AF250-10

AF250-12